

WATERBATH - DOUBLE WALLED. DIGITAL.

- Construction : Double Walled. Inside made of stainless steel. Outer made of CRC / S.S. Powder Coated. Gap between the wall filled with Glass Wool.
- Temperature Range : 5° C above ambient to 100° C.
- Controlled By : Dual Display Micro Processor Based Digital Temperature Controller cum Indicator.
- Temp. Control Accuracy : ± 1° C or better.
- Standard Supply : Complete with stainless steel lid. Three Core Wire with Plug.
- Operated On : 230 V, 50 Hz, Single Phase, AC Supply.



ORDER CODE	Size LxWxD (Cm)	INNER CHAMBER	OUTER CHMABER	STIRRER
AIC-WBDD-403015S / AIC-WBDD-403015SS	40x30x15	SS	CRC Powder Coated / SS	Yes
AIC-WBDD-302517S / AIC-WBDD-302517SS	35x30x25	SS	CRC Powder Coated / SS	Yes

NOTE: These Waterbaths can be supplied with 06/12 concentric rings arrangements.



WATERBATH - DOUBLE WALLED. THERMOSTATIC.

- Construction : Double Walled. Inside made of stainless steel. Outer made of CRC / S.S. Powder Coated. Gap between the wall filled with Glass Wool.
- Temperature Range : 5° C above ambient to 100° C.
- Controlled By : Sensitive Thermostat.
- Temp. Control Accuracy : ± 2° C.
- Standard Supply : Complete with stainless steel lid. Three Core Wire with Plug. (Without Thermometer).
- Operated On : 230 V, 50 Hz, Single Phase, AC Supply.

ORDER CODE	Size LxWxD(Cm)	INNER CHAMBER	OUTER CHMABER
AIC-WBD-403015S / AIC-WBD-403015SS.	40x30x15	SS	CRC Powder Coated / SS
AIC-WBD-302517S / AIC-WBD-302517SS.	30x25x17.5	SS	CRC Powder Coated / SS
AIC-WBD-303025S / AIC-WBD-303025SS.	30x30x25	SS	CRC Powder Coated / SS
AIC-WBD-353520S / AIC-WBD-353520SS.	35x35x20	SS	CRC Powder Coated / SS
AIC-WBD-352525S / AIC-WBD-352525SS.	35x25x20	SS	CRC Powder Coated / SS
AIC-WBD-252020S / AIC-WBD-252020SS.	25x20x20	SS	CRC Powder Coated / SS

NOTE: These Waterbaths can be supplied with 06/12 concentric rings arrangements.