

WATERBATH - CONSTANT TEMPERATURE.



Construction : Double walled. Inside made of Stainless Steel, Outer made of CRC Powder

Coated / S.S. Glass Wool insulation.

Temperature Range : From 5° C above ambient to 100° C.

Temp. Controlled By : Dual Display Microprocessor Based

Digital Temperature Indicator cum

Controller.

Temp. Control Accuracy : $\pm 0.5^{\circ}$ C.

Standard Supply : Complete with a Stirrer mounted on a

base and fitted on the side of the bath at the top. Three Core Wire with Plug.

Operated On : 230 V, 50 Hz, Single Phase, AC Supply.

ORDER CODE	Size LxWxD (Cm)	INNER Chamber	OUTER CHMABER	STIRRER
AIC-CTB-373025S / AIC-CTB-373025SS.	37.5x30x25	SS	CRC Powder Coated / SS	Yes
AIC-CTB-353025S / AIC-CTB-353025SS.	35x30x25	SS	CRC Powder Coated / SS	Yes
AIC-CTB-303025S / AIC-CTB-303025SS.	30x30x25	SS	CRC Powder Coated / SS	Yes
AIC-CTB-353520S / AIC-CTB-353520SS.	35x35x20	SS	CRC Powder Coated / SS	Yes
AIC-CTB-352525S / AIC-CTB-352525SS.	35x25x20	SS	CRC Powder Coated / SS	Yes
AIC-CTB-252020S / AIC-CTB-252020SS.	25x20x20	SS	CRC Powder Coated / SS	Yes

WATERBATH - LOW TEMPERATURE.

Construction : Double walled. Inside made of

Stainless Steel 304, Outer made of M.S. Powder Coated.

PUFF insulation.

Temperature Range : From 5° C to 60° C.

Temp. Controlled By : Dual Display Microprocessor

Based Digital Temperature

Indicator cum Controller.

Temp. Control Accuracy : $\pm 1^{\circ}$ C.

Standard Supply : Complete with a Stirrer fitted on

the side of the bath at the top.

Three Core Wire with Plug.

Operated On : 230 V, 50 Hz, Single Phase, AC

Supply.



ORDER CODE	Size LxWxD (Cm)	INNER CHAMBER	OUTER CHMABER	STIRRER
AIC-LTB-202020S / AIC-LTB-202020SS.	37.5x30x25	SS	CRC Powder Coated / SS	Yes
AIC-LTB-252020S / AIC-LTB-252020SS.	35x30x25	SS	CRC Powder Coated / SS	Yes

NOTE: Other Sizes Also Can Be Made On Request.